

HAND EXTRUDER

booster EX3 Plus

High output. Precise control. Built for demanding jobs.

The booster EX3 Plus is a high-performance hand extruder for professional plastic welding applications. With 3000 W power and compatibility with 3–4 mm welding rod, it delivers up to 3.4 kg/h material output. The internal air guide and open-loop air temperature control ensure reliable performance, while the display and LED working light provide maximum control and visibility – all in a robust, ergonomic design.

**3000 W
POWER**Strong extrusion
performance**Ø 3–4 MM ROD**Supports common
welding rod sizes**UP TO 3.4 KG/H**High material
output**DISPLAY &
LED LIGHT**Better visibility
and control**ERGONOMIC
DESIGN**Comfortable
handling on site

TECHNICAL DATA

Article	802.930	
Voltage	230 V	
Frequency	50/60 Hz	
Power	3000 W	
Welding rod	Ø 3–4 mm / 0.12–0.16 in	
Material output Ø 3 mm	2.5 kg/h	5.51 lb/h
Material output Ø 4 mm	3.4 kg/h	7.49 lb/h
Air guide	Internal	
Air temperature control	Open loop	
Display	Yes	
LED Working light	Yes	
Length	645 mm	25.39 in
Width	247 mm	9.72 in
Height	265 mm	10.43 in
Power cable length	3 m	9.84 ft
Plug	EU, 3 poles, 16A	
Noise emission level	74 dB (A)	
Protection class	II	
Country of origin	P.R. China	

PRODUCT INFORMATION

Article no.
802.930

KEY DETAILS



Internal air guide



Open-loop temperature control



Display



LED working light



EU 3-pole 16A plug

APPLICATIONS



Plastic tank fabrication



Geomembrane welding



Pipe and fitting production



Custom plastic fabrication