

WELDY

WELD
ROOFS
BUILD
LAST

PROFESSIONAL
RESULTS
ANYWHERE

HOT-WEDGE WELDING MACHINE

miniwelder roof2

Lightweight. Tolerant. Economical.

The miniwelder roof2 is a lightweight and easy to use hot-wedge welding machine for all pitched roofs. It is ideal for PVC and TPO inner roof membranes up to 1 mm. The inner roof membrane does not flap when welding as no blower air is required. Save money on toxic solvent-welding agents and benefit from safe and reliable welding performance.

*Reliable
Roof Welding
Made Easy*



LIGHTWEIGHT & PORTABLE

Weighs only 4 kg



SAFE CONTACT WELDING

Aluminum
hot wedge



WIDE APPLICATION RANGE

For PVC and TPO
up to 1 mm



ALL-WEATHER PERFORMANCE

Works at high and
low temperatures



CLEAN & ECONOMICAL

No toxic solvent-
welding agents
required

TECHNICAL DATA

Voltage	120 / 230	V~
Frequency	50 / 60	Hz
Max. power	800	W
Temperature	60 – 480	°C
Hot wedge material	aluminum	-
Hot wedge width	40	mm
Max. overlap	80	mm
Speed	0.4 – 7.5	m/min
Dimensions (L x W x H)	228 x 228 x 170	mm
Weight (without guide bar)	4	kg
Protection class	I	-

APPLICATIONS




PITCHED ROOFS

Ideal for all
pitched roofs



PREFABRICATION

Perfect for
prefabrication



MEMBRANE WELDING

PVC and TPO
inner roof membranes
up to 1 mm



OUTDOOR USE

Suitable for high
and low outdoor
temperatures



DELIVERY CONTENTS

- Instruction manual
- Transport box
- Guide bar
- Allen key
- Cleaning brush



READY FOR THE JOB

A reliable, lightweight solution
for professional roofing
applications.

SMART SOLUTIONS
FOR A STRONGER TOMORROW

BUILT FOR
REAL WORK